



## U.S. Environmental Protection Agency

# Ground Water & Drinking Water

[Recent Additions](#) | [Contact Us](#) | [Print Version](#)

Search:  [GO](#)

[EPA Home](#) > [Water](#) > [Ground Water & Drinking Water](#) > Technical Factsheet on: TETRACHLOROETHYLENE

**Drinking Water and Health Basics**

**Frequently Asked Questions**

**Local Drinking Water Information**

**Drinking Water Standards**

**List of Contaminants & MCLs**

**Regulations & Guidance**

**Public Drinking Water Systems**

**Source Water Protection**

**Underground Injection Control**

**Data & Databases**

**Drinking Water Academy**

**Safe Drinking Water Act**

**National Drinking Water Advisory Council**

**Water Infrastructure Security**



Technical Factsheet on: TETRACHLOROETHYLENE

[List of Contaminants](#)

As part of the Drinking Water and Health pages, this fact sheet is part of a larger publication:

### National Primary Drinking Water Regulations

#### Drinking Water Standards

MCLG: zero mg/L

MCL: 0.005 mg/L

HAL(child): 1- to 10-day: 2 mg/L; Longer-term: 1 mg/L

#### Health Effects Summary

**Acute:** EPA has found tetrachloroethylene to potentially cause the following health effects from acute exposures at levels above the MCL: detrimental effects to liver, kidney, and central nervous system.

Drinking water levels which are considered "safe" for short-term exposures: For a 10-kg (22 lb.) child consuming 1 liter of water per day: a one- to ten-day exposure to 2 mg/L; upto a 7-year exposure to 1 mg/L.

**Chronic:** Tetrachloroethylene has the potential to cause the following health effects from long-term exposures at levels above the MCL: detrimental effects to liver, kidney, and central nervous system.

**Cancer:** There is some evidence that tetrachloroethylene may have the potential to cause cancer from a lifetime exposure at levels above the MCL.

#### Usage Patterns

Production of tetrachloroethylene has decreased: from 736 million lbs. in 1978 to 405 million lbs in 1986.

In 1989 it was estimated that industries consumed tetrachloroethylene as follows: Dry cleaning and textile processing, 50%; chemical intermediate (mostly fluorocarbon F-113), 28%; industrial metal cleaning, 9%; exports, 10%; other, 3%.

The greatest use of tetrachloroethylene is in the textile industry for processing, finishing, sizing, and as a component of aerosol dry-cleaning products.

Other uses include: an intermediate in the synthesis of fluorocarbons, an insulating/cooling fluid in electric transformers, in typewriter correction fluids, as veterinary medication against worms, once used as grain protectant/fumigant.

#### Release Patterns

Major releases of tetrachloroethylene are: via vaporization losses from dry cleaning and industrial metal cleaning; wastewater, particularly from metal finishing, laundries, aluminum forming, organic chemical/plastics manufacturing and municipal treatment plants. It is also

estimated that emissions account for approximately 90% of the tetrachloroethylene produced in the United States.

Water pollution can occur from tetrachloroethylene leaching from vinyl liners in asbestos-cement water pipelines for water distribution, and during chlorination water treatment, where it can be formed in small quantities.

From 1987 to 1993, according to EPA's Toxic Chemical Release Inventory, tetrachloroethylene releases to land and water totalled over 1 million lbs., of which about 75 percent was to land. These releases were primarily from alkali and chlorine industries which use tetrachloroethylene in making other chemicals. The largest releases occurred in Louisiana and South Carolina.

### **Environmental Fate**

If PCE is released to soil, it will be subject to evaporation into the atmosphere and to leaching to the groundwater. Tetrachloroethylene was slightly adsorbed on sand and clay minerals. The Henry's adsorption coefficients were approximately in proportion to the organic content of the soil samples. Based on the reported and estimated Koc's (209 to 1685), tetrachloroethylene will be expected to exhibit low to medium mobility in soil and therefore may leach slowly to the groundwater.

There is evidence that slow biodegradation of PCE occurs under anaerobic conditions when the microorganisms have been acclimated. In experiments using continuous-flow laboratory methanogenic column with well acclimated mixed cultures and a 2-day detention time, there was an average PCE removal rate of 76%. Removal of 86% PCE occurred in a methanogenic biofilm column (8 weeks of activation followed by 9-12 weeks of acclimation). In a microcosm containing muck from an aquifer recharge basin, 72.8% loss was observed in 21 days against 12-17% in controls. In one field ground water recharge project, degradation was observed in the 50 day recharge period.

If PCE is released to water, it will be subject to rapid volatilization with estimated half-lives ranging from <1 day to several weeks. Measured volatilization half-lives in a mesocosm simulating Narraganset Bay, RI were 11 days in winter, 25 days in spring, and 14 days in summer.

PCE will not be expected to significantly biodegrade in water or adsorb to sediment. PCE will not be expected to significantly hydrolyze in soil or water under normal environmental conditions (half-life 9 months at 25 deg C).

If PCE is released to the atmosphere, it will exist mainly in the gas-phase and it will be subject to photooxidation with estimates of degradation time scales ranging from an approximate half-life of 2 months to complete degradation in an hour. Some of the PCE in the atmosphere may be subject to washout in rain based on the solubility of PCE in water and the fact that PCE has been detected in rain.

Based on the reported and estimated BCF's, tetrachloroethylene will not be expected to significantly bioconcentrate in aquatic organisms. BCFs of 39 to 49 were measured in fish; a BCF of 226 was estimated from octanol water partition coefficient.

Major human exposure is from inhalation of contaminated urban air, especially near point sources such as dry cleaners, drinking contaminated water from contaminated aquifers and drinking water distributed in pipelines with vinyl liners, and inhalation of contaminated occupational atmospheres in metal degreasing and dry cleaning industries.

### **Chemical/Physical Properties**

CAS Number: 127-18-4

Color/ Form/Odor: Colorless liquid with mildly sweet, chloroform-like odor; available in

many forms, from worm pills to dry-cleaning grades containing various stabilizers.

M.P.: -19 C B.P.: 121 C

Vapor Pressure: 18.47 mm Hg at 25 C

Octanol/Water Partition (Kow): Log Kow = 3.40

Density/Spec. Grav.: 1.62 at 20 C

Solubility: 0.15 g/L of water at 25 C; Slightly soluble in water

Soil sorption coefficient: Koc = 210 (exp.) to 238 (est.); low to moderate mobility in soil

Odor/Taste Thresholds: Taste threshold in water is 0.3 mg/L

Bioconcentration Factor: BCFs of 39 to 49 reported in fish; not expected to bioconcentrate in aquatic organisms.

Henry's Law Coefficient: N/A

Trade Names/Synonyms: Ethylene tetrachloride, Perchloroethylene, PCE, Ankilostin, Didakene, Fedal-un, Nema, Perclene, Persec, Tetlen, Tetracap, Tetraleno, Tetropil, Antisal 1, Dow-per, Perawin, Perchlor, Percosolv, Perk, Perklone, Tetraguer, Tetralex, Tetravec

### Other Regulatory Information

Monitoring:

-- For Ground/Surface Water Sources:

Initial Frequency- 4 consecutive quarterly samples during initial compliance period (1993-1995)

Repeat Frequency- If no detects in initial samples GW systems must take annual samples during 1996-1998 compliance period and triennial samples thereafter; SW systems must take annual samples.

-- Triggers - Return to quarterly monitoring if detect at > 0.0005 mg/L, until primacy State determines otherwise

### Analysis

**Reference Source**  
EPA 600/4-88-039

**Method Numbers**  
502.2; 524.2; 551

**Treatment/Best Available Technologies:** Granular Activated Charcoal and Packed Tower Aeration

### Toxic Release Inventory - Releases to Water and Land, 1987 to 1993 (in pounds):

TOTALS (in pounds)		Water 297,602	Land 750,104
<b>Top Five States*</b>			
LA	23,639	610,518	
SC	104,728	0	
NH	62,150	0	
NC	42,192	13,102	
IL	0	40,500	

TX	36,144	720	
OH	0	32,170	
IN	1,300	27,000	
CO	0	11,000	
IA	5,112	0	
<b>Major Industries*</b>			
Alkalis, chlorine		63,472	611,242
Leather tanning, finishing		62,150	0
Cotton fabric finishing		51,577	0
Misc textile finishing		48,082	2,000
Knit outwear mills		45,808	0
Misc. apparel, access.		0	40,500
Transportation Equip.		3,750	27,000
Ammunition		0	20,575
Misc Chem. preparations		0	11,102
Petroleum refining		0	11,000
Ordnance, accessories		0	10,100

\* Water/Land totals only include facilities with releases greater than a certain amount - usually 1000 to 10,000 lbs.

### For Additional Information

EPA can provide further regulatory or other general information:  
EPA Safe Drinking Water Hotline - 800/426-4791

Other sources of toxicological and environmental fate data include:  
Toxic Substance Control Act Information Line - 202/554-1404  
Toxics Release Inventory, National Library of Medicine - 301/496-6531  
Agency for Toxic Substances and Disease Registry - 404/639-6000

### [List of Contaminants](#)

[Safewater Home](#) | [About Our Office](#) | [Publications](#) | [Links](#) | [Office of Water](#) | [En Español](#)

---

[EPA Home](#) | [Privacy and Security Notice](#) | [Contact Us](#)

Last updated on Tuesday, November 21st, 2006  
URL: <http://www.epa.gov/OGWDW/dwh/t-voc/tetrachl.html>